

Value Guide: Anchors

Name	Weight	Setting Rank			Holding Power				Average	
		Sand	Mud	Combined	Sand	Rank	Mud	Rank	Holding	Rank
Barnacle	25 lbs.	16	9 Tie	12 Tie	355 lbs.	9	800 lbs.	1	577 lbs.	4
Bruce	22 lbs.	3	2 Tie	1	307 lbs.	11	550 lbs.	8	429 lbs.	10
Bulwagga	17 lbs.	1	8	4 Tie	816 lbs.	2	680 lbs.	3	748 lbs.	2
Claw	22 lbs.	8	2 Tie	4 Tie	283 lbs.	14	520 lbs.	9	401 lbs.	12
CQR	35 lbs.	15	2 Tie	9	583 lbs.	3	760 lbs.	2	672 lbs.	3
Danforth Deepset II	20 lbs.	14	15	14	363 lbs.	8	640 lbs.	5	502 lbs.	6
Delta	22 lbs.	13	1	7	496 lbs.	4	610 lbs.	6	553 lbs.	5
Fortress FX-16	10 lbs.	9	13	11	471 lbs.	5	420 lbs.	12	446 lbs.	8
Hans C-Anchor	15 lbs.	17	12	15	0 lbs.	17	350 lbs.	15	175 lbs.	15
Herreshoff Bronze	17 lbs.	6	—	—	300 lbs.	12	—	—	—	—
Hydro-Dyne	10 lbs.	Failed	—	—	—	—	—	—	—	—
Nautical Engineering	20 lbs.	11	14	12 Tie	235 lbs.	15	390 lbs.	14	313 lbs.	14
Seagrip	33 lbs.	12	—	—	200 lbs.	16	—	—	—	—
Supermax (Adj. shank)	26 lbs.	7	2 Tie	3	410 lbs.	7	430 lbs.	11	420 lbs.	11
Supermax	26 lbs.	5	2 Tie	2	350 lbs.	10	400 lbs.	13	375 lbs.	13
Spade Model 80	16.5 lbs.	2	7	6	1,000 lbs.	1	660 lbs.	4	830 lbs.	1
Vetus	12 lbs.	4	9 Tie	8	285 lbs.	13	590 lbs.	7	438 lbs.	9
West Performance ²	25 lbs.	10	11	10	456 lbs.	6	460 lbs.	10	458 lbs.	7